

Product Specifications

Product: Meter/Pit Insulation Plug

Product Characteristics:

Plug Body: 1.2# laminated closed cell polyethylene foam, USA origination
R-value 2.5 per inch, Sediment and water resistant
MP2 Pit Plugs have a minimum height of 2"
MP4 Pit Plugs have a minimum height of 4"
MP6 Pit Plugs have a minimum height of 6"

Handle: 3/8" Hollow Braid Polypropylene, USA sourced
Tensile strength: 1800 lbs., safe working load: 306 lbs.

Handle connection: Long bury spliced with heat weld. The handle is installed through the body of the plug and heat welded. The polypropylene handle is highly visible and is resistant to rot, mildew, oils, gas and most chemicals.

Size	2" Thick	4" Thick	6" Thick	4" Thick MDL
15	MP2-15	MP-15	MP6-15	WMP-15
18	MP2-18	MP-18	MP6-18	WMP-18
21	MP2-21	MP-21	MP6-21	WMP-21
24	MP2-24	MP-24	MP6-24	WMP-24
27	MP2-27	MP-27	MP6-27	WMP-27
30	MP2-30	MP-30	MP6-30	WMP-30
36	MP2-36	MP-36	MP6-36	WMP-36
42	MP2-42	MP-42	MP6-42	WMP-42
48	MP2-48	MP-48	MP6-48	WMP-48



*ID of pipe is needed for the best fit. Custom sizes available.



Made in USA
www.ckrproducts.com
SARTELL, MN 56377 USA